

3M

沐浴過濾器 Shower Filter

符合美國
FDA NSF
濾殼標準 · 濾芯認證



From the Fortune 500
由財富500強企業呈獻



50,000公升超大濾量
50,000L Large Filtration Capacity



呵護秀髮 - 降低餘氯及過濾雜質，
使髮質不易乾旱
Hair care - Moisturize hair by reducing
chlorine taste and impurities



保護肌膚 - 避免餘氯對肌膚
的刺激和傷害
Skin Care - lessen skin damage and
irritation by removing chlorine



降低餘氯，過濾雜質
Reduce chlorine taste and filter impurities

榮獲美國國家衛生基金會認證
NSF International



NSF/ANSI Std. 42 感官效應 Drinking Water Treatment Units - Aesthetic Effects

沐浴過濾器

Shower Filter

濾殼選用原料符合FDA

Housing - FDA Compliant Materials

符合FDA CFR21 美國食品藥物管理局要求。

Manufactured with FDA CFR-21 Food Grade Compliant Materials

濾料擁有美國認證NSF

Filtration Media - Certified by NSF International

美國國家衛生基金會認證。高純度KDF過濾材質通過NSF42標準認證。過濾性能依照美國NSF沐浴過濾器標準177檢測合格。



This high concentration KDF is certified by NSF International 42 Standard.

Tested in accordance with NSF/ANSI 177 Shower Filtration Systems Standard.



安裝方法

Installation Method



規格

Specification

產品型號 Model	沐浴過濾器 Shower Filter
有效過濾水量 Capacity	50,000公升liters
流量 Flow Rate	8公升/分鐘 lpm
適用水溫 Operating Temperature	5°C - 50°C
適用水壓 Operating Pressure	30-125psi
尺寸 (直徑 x 長度) Dimension (Diameter x Height)	64.4mm x 176.4mm



有效降低餘氯，且過濾壽命長。

Effectively reduce chlorine taste and extend cartridge

使用須知:

- 1.如懷疑水源受污染或未經消毒，請勿使用本產品。
- 2.安裝及使用前，請先閱讀安裝及操作指引，避免因漏水而引致之任何財物損失。
- 3.本公司並不承擔任何因安裝或保養失當所造成之產品故障。

Instructions:

1. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection.
2. To avoid property damage due to water leakage, you must read the installation and operating manual before installation.
3. 3M will not be liable for system failure due to improper maintenance and installation.

* 實際產品顏色可能與以上產品圖片略有不同。規格如有變更，恕不另行通知。

Actual colours may vary slightly from the items show above. Specification is subject to change without prior notice.

* 濾芯總處理量依照NSF標準177進行測試：以每分鐘8公升之流速，在2ppm餘氯40°C水溫測試；當達到50,000公升處理量時，仍有50%以上的去除率。

The filtration capacity was tested in accordance with NSF/ANSI 177 Shower Filtration Systems Standard. In the condition that water flow rate at 8 lpm, chlorine at 2ppm, water temperature at 40°C; the water filtration capacity can meet 50,000L and the effectiveness of the filter effectiveness can meet 50% or above.



濾水系統

3M香港有限公司

香港屈臣道15號維多利中心五字樓

電話: 2806 6111

www.3M.com/hk/waterfilter